A4 Mono Printer and MFP



RICOH P 311 M 320F





Stability and Performance

Ensure uninterrupted workflow with print-on-demand from anywhere functionality

Easy to change, long-lasting print cartridges

RICOH P 311 and M 320F offer an All-in-One print cartridge with a long-lasting 7,000 print yield. When you do need to replace the cartridge, there's no disruption to your workflow. Simply slot in the new one via the convenient full front-access design.





*Image shown is with optional tray

Easy document sharing digitally

The feature-rich RICOH M 320F multi-function printer is made for easy sharing of all your important information. The 35-sheet Automatic Reversing Document Feeder (ARDF) allows you to scan and send a full-colour presentation to colleagues for review instantly via multiple Scan-to capabilities, including Scan-to-Email, FTP, Folder, USB drive and more.

Work from anywhere

Access and share all your documents even when not in the office via the RICOH Smart Device Connector app on your mobile device. Mopria® or AirPrint® lets you send print jobs directly to your RICOH printer from your mobile phone. Once you're back in the office, simply pair your Android® device via the Near Field Communications (NFC) tag on the printer to authenticate and transfer information and print.





Security is in our DNA

Recognising your need to keep your data secure, we've added robust security layers. Protect confidential documents from unauthorised viewing with the Locked Print function. Network encryption also ensures data transmission remains secure.

RICOH P 311 / M 320F

MAIN SPECIFICATIONS

MODEL		RICOH P 311	RICOH M 320F
GENERAL			
Configuration		Desk	top
Technology		Laser (Mono)	
Function(s)		Print	Print, Copy, Scan, Fax
Display panel		4-Line operation LCD	4.3" colour touch panel
Processor		350 MHz	400 MHz
Memory		128 MB	256 MB
Mobile capability		RICOH Smart Device Connector, Apple AirPrint®, Mopria®	
Printer language		PCL5e, PCL6, PostSi	· · · · · · · · · · · · · · · · · · ·
Network protocol		TCP/ 10Base-T/100Base-Tx (Ethernet).	
Operating system PRINTER	Standard	USB 2.0 Type A x 1— rear, USB 2.0 Type B— rear, NFC tag	10Base-T/100Base-Tx (Ethernet) USB 2.0 Type A x 2—1 x rear & 1x front, USB 2.0 Type B x 1— rear, NFC tag
	Optional	IEEE 802.11a/b/g/n/ac (Wire	
	Windows®	Windows® 8.1, Windows® 10, Windows® Server 2012, Windows® Server 2012R2, Windows® Server 2016, Windows® Server 2019	
	Mac	Mac OS v10.10 - v11 Linux	
	Other	Linux	
		Aut	
Duplex printing Print speed (A4)		Auto 32 ppm (Simplex), 13 ppm (Duplex)	
First print out time		3.2 ppm (simplex), 13 ppm (ouplex) 7.1 seconds	
Warm up time		26 seconds or less	30 seconds or less
warm up time		600 x 600 dp	I .
Print resolution		Windows®: 600 x 600 dpi, 1,200 x 600 dpi, 1,200 dpi MAC: 600 x 600 dpi Linux: 600 x 600 dpi	
Average print volume		700 - 5,800 pages	
Duty cycle		35,000 pages/month	
COPIER			
Copy speed (A4)		-	Up to 32 ppm
Document feeder type		-	Automatic Reversing Document Feeder
Document feeder capacity		-	35 sheets
Resolution		-	300 x 600 dpi (ARDF), 600 x 600 dpi (Platen)
Multiple copy		-	Up to 99
Copy features		-	Zoom Range: 25%-400%, Image density: 5 levels, Image quality: Text, Photo, Mixe
			Combined Copy, Memory Copy, ID Card Copy, Series Copy
CANNER			M 42:
Scan speed (A4 ARDF) Resolution		-	Mono: 13 impressions/minute, Colour: 4.5 impressions/minute
Original size		-	600 x 600 dpi (ARDF), 1,200 x 1,200 dpi (Platen), 19,200 x 19,200 dpi (PC TWAIN) A4
Bundled drivers			Network TWAIN, WIA
Scan to		-	Scan to email, Scan to folder, Scan to FTP, Scan to USB, TWAIN scanning
FACSIMILE			Scarr to chian, scarr to rouce, scarr to 111, scarr to 050, 147AIN scarring
Circuit		<u>-</u>	PSTN, PABX
Compatibility		_	T.30 (ITU-T SuperG3)
			Horizontal: 200 dpi-8dots/mm,
Resolution		-	Vertical 100 dpi-3.85dots/mm, 200 dpi-7.7dots/mm
Transmission speed		-	33.6 Kbps—2,400 bps with automatic shift down
Compression method		-	MH, MR, MMR
Reception features		-	Automatic, Paperless fax, Manual, Main scan auto reduction
Other supported features		-	Quick dial—8 (20 digits for name, 40 digits for numbers), Speed dial—100 (20 digits name, 40 digits for numbers), Label registration for Quick/Speed, Redial—automatic manual, Redial interval time—2 selections (5 minutes: default, 6 minutes), Only red last number, Direct fax number entry
SECURITY			
Authentication		Locked	Print
PAPER HANDLING Recommended paper size Paper input capacity Paper output capacity Paper weight		A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican Oficio, Indian Legal, Envelopes, Australian Foolscap 250 sheets (Bypass: 50 sheets), Maximum: 300 sheets	
		Paper Bank PB1130: 250 she	ets, Maximum 550 sheets 50 sheets
		125 sheets 52 to 16	I .
		COLOGY	
Dimensions (W x D x H)		370 mm x 392 mm x 262 mm	405 mm x 392 mm x 420 mm
Weight		Less than 13.0 kg	Less than 18.0 kg
Power consumption (Max)			
Ready mode		1,025 W (Asia Pacific 63.8 W (Asia Pacific), 64.9 W (Taiwan)	65.7 W (Asia Pacific), 65.7 W (Taiwan)
,		0.72 W (Asia Pacific), 64.9 W (Taiwan)	0.87 W (Asia Pacific), 65.7 W (Taiwan)
normy cause (Cl)		0.72 W (ASIA PACITIC), 0.66 W (IAIWAN) 0.87 W (ASIA PACITIC), 0.8 W (IAIWAN) 220–240 V, 50/60 Hz, 4.3 Amps (Asia Pacific), 110 V, 60 Hz, 8.5 Amps (Taiwan)	
		22U-24U V, 5U/6U HZ, 4.3 Amps (Asia Pa	uncj, 110 v, оо пz, 8.5 Amps (тагwan)
Power source			
Power source CONSUMABLES	0.45		
Energy saver (Sleep) Power source CONSUMABLES AIO toner cartridges (k		Black: Approx.	7,000 pages
Power source CONSUMABLES AIO toner cartridges (k Consumable yield mea	suring method ISO/IEC 1975	2	7,000 pages
Power source CONSUMABLES AlO toner cartridges (k Consumable yield mea Shipped with Starter To	suring method ISO/IEC 1975		7,000 pages
Power source CONSUMABLES AIO toner cartridges (k Consumable yield mea	suring method ISO/IEC 1975	2	













